






## UPS Techno PRO

Line Interactive POWER SUPPLY TP Series  
UPS 3000VA / 4000VA


**230 VAC**


### SPECIFICATION

MODEL	TP3000LI	TP4000LI
CAPACITY	3000VA/1800W	4000VA/2400W
INPUT		
NOMINAL INPUT VOLTAGE	110/120VAC OR 220/230/240 VAC	
OPERATING VOLTAGE RANGE	81-145VAC/162-290 VAC	
OPERATING FREQUENCY RANGE	50/60 HZ (1±10%)	
OUTPUT		
OUTPUT VOLTAGE RANGE (BATT. MODE)	SIMULATED SINEWAVE AT NOMINAL VOLTAGE ±10%	
FREQUENCY RANGE (BATT. MODE)	50 HZ OR 60 HZ ± 1 HZ	
TRANSFER TIME	TYPICAL 2-6 MS, 10MS MAX.	
BATTERY		
BATTERY TYPE & NUMBER	12 V / 7.2 AH X 4	12 V / 7.2 AH X 6
TYPICAL RECHARGE TIME	6-8 HOURS ( TO 90% CAPACITY)	
PROTECTION		
TYPICAL RECHARGE TIME	OVERLOAD AND OVERCHARGE PROTECTION	
INDICATORS		
TYPICAL RECHARGE TIME	AC MODE, BATTERY MODE, LOAD LEVEL, BATTERY LEVEL	

## UPS Techno PRO

Line Interactive POWER SUPPLY TP Series  
 UPS 3000VA / 4000VA

ALARM		
BATTERY MODE	SOUNDING EVERY 10 SECOND	
BATTERY LOW	SOUNDING EVERY SECOND	
OVERLOAD	SOUNDING EVERY 0.5 SECOND	
BATTERY REPLACEMENT ALARM	SOUNDING EVERY 2 SECONDS	
FAULT	CONTINUOUSLY SOUNDING	
Management		
USB & RS-232 PORT (OPTIONAL)	USB OR RS232(SUPPORTS WINDOWS ,LINUX, UNIX, AND MAC)	
LCD	UPS STATUS, INPUT/OUTPUT VOLTAGE, INPUT/OUTPUT FREQUENCY, LOAD LEVEL, BATTERY CAPACITY, AND WARNING OR FAULT ERROR CODE.	
PHYSICAL		
DIMENSION W X D×H (MM)	158×380×198	
NET WEIGHT (KG)	10.5	13.5
ENVIRONMENT		
OPERATING TEMPERATURE	0C~40C	
HUMIDITY RANGE	20~95%RH @ 0~40C (NON CONDENSING)	
NOISE LEVEL	<45DB (1 METER FROM SURFACE)	
STANDARDS		
SAFETY	IEC/EN62040-1,IEC/EN62477-1	
EMC	IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,IEC61000-4-8	